



---

# ET-L10

Data capture  
at a glance

---



# Robust and Smart

Who says mobile data collection can't be smart? ET-L10 is a full-fledged mobile data capturing device for scanning and reading 1D and 2D barcodes within seconds.

The latest Android 9 operating system and a large 5.7-inch full-touch display mean that it is just as versatile and intuitive to use as a smartphone.

The professional all-rounder is ideally suited for use in the retail area or the field service.



LARGE DISPLAY

**5,7"**

EXTRA SLIM

**15,5** mm

LIGHT

**240** g

CPU		Qualcomm SDM 450 (Octa Core 1.8GHz)
OS		Android 9
Memory	RAM	2 GB
	FROM	16 GB
Display	LCD	5.7 -inch (145 mm) transmissive color TFT LCD (720 x 1,440 pixels HD+)
	Touch Panel	Capacitive touch panel
Imager	Scanner	CMOS-Imager, resolution 832 x 640 pixels
	Readable Codes (1D)	UPC-A, UPC-E, EAN8 (JAN8), EAN13 (JAN13) Codabar (NW7), Code39, Interleaved2of5 (ITF), MSI, Code93, Code128 (GS1-128(EAN128)), GS1 DataBar-Omnidirectional (RSS-14), GS1 DataBar Limited (RSS Expanded), GS1 DataBar Truncated (RSS-14 Truncated)
	Readable Codes (2D Stacked)	PDF417, Micro PDF, GS1 DataBar Stacked Omnidirectional (RSS-14 Stacked Omnidirectional), GS1 DataBar Expanded Stacked (RSS Expanded Stacked), GS1 DataBar Stacked (RSS-14 Stacked)
	Readable Code (2D Matrix)	Aztec, DataMatrix, Maxicode, QR-Code Micro QR, Han Xin Code
Digital Camera	Back	13 magapixel, autofocus, LED-Flash, flash light (torch)
RFID/NFC Functionality	NFC Standards	ISO14443 Type A/B, Mifare®, FeliCa®, ISO15693
Wireless Communication	Bluetooth®	Ver. 5.0 + EDR/LE
	WLAN (WiFi)	IEEE 802.11 a/b/g/n/ac, IEEE 802.11 d
	WWAN	GSM, W-CDMA, LTE
	GPS	GPS, GLONASS and BeiDou
Durability	Drop Durability	1.5m onto concrete
	Dust and Water Resistance	Protection class IP65
Sensor		Accelerometer, illumination sensor, proximity sensor, fingerprint sensor
Extensions	USB	USB 2.0 (Client), USB Type-C
	SD card slot	microSD (SDHC)
	SIM card slot	nano SIM
Power	Main Power	Lithium-ion battery, Operating period: Approx. 12 hours
	Capacity	Integrated Lithium-ion battery with 4,000 mAh
External Dimensions (W x D x H)		Approx. 78.8 x 162 x 15.5mm
Operating Temperature		-10 °C to +50 °C
Weight		Approx. 240 g (including battery)

## Accessoires



Cradle, only charging function  
(incl. AC Adapter) HA-T30CHG



Screen protection sheets, 10pcs  
HA-T90PS1

Android, Google Maps, Google Mail, Google Play, Google Drive, Hangout and Chrome are registered trademarks of the Google, Inc., USA. MIFARE is a registered trademarks of the NXP B.V. The Bluetooth® trademark is owned by Bluetooth SIG, Inc., U.S.A. and licensed to CASIO Computer Co., Ltd.. Other Product- and company names are either trademarks or registered trademarks of the respective owners. The design and specifications may be varied without notice. The color display of pictures may vary from the actual colors. Screen images are simulated representations. The specifications in the table above are as of October 2019.

**Casio Europe GmbH**  
Casio-Platz 1  
22848 Norderstedt, Germany  
solutions@casio.de  
+49 (0)40 528 65-407  
www.casio-solutions.com